




# TP-Link TL-SG105S Unmanaged Gigabit Ethernet (10/100/1000) Schwarz

Marke : TP-Link

Artikel-Code: TL-SG105S V2

Produktname : TL-SG105S

TP-Link TL-SG105S. Switch-Typ: Unmanaged. Basic Switching RJ-45 Ethernet Ports-Typ: Gigabit Ethernet (10/100/1000), Anzahl der basisschaltenden RJ-45 Ethernet Ports: 5. Vollduplex. MAC-Adressentabelle: 2000 Eintragungen, Routing-/Switching-Kapazität: 10 Gbit/s. Netzstandard: IEEE 802.1p, IEEE 802.3, IEEE 802.3ab, IEEE 802.3u, IEEE 802.3x. Wandmontage



| Management-Funktionen                              |   | Design                               |               |
|--|---|--------------------------------------|---------------|
| Switch-Typ *                                       | Unmanaged   | LED-Anzeigen                         | ✓             |
| Quality of Service (QoS) Support                   | ✓   | Wandmontage                          | ✓             |
| Anschlüsse und Schnittstellen                      |   | Zertifizierung                       | CE, FCC, RoHS |
| Anzahl der basisschaltenden RJ-45 Ethernet Ports * | 5   | Leistungen                           |               |
| Basic Switching RJ-45 Ethernet Ports-Typ *         | Gigabit Ethernet (10/100/1000)                                  | Plug & Play                          | ✓             |
| Anzahl Gigabit Ethernet (Kupfer) Anschlüsse        | 5   | Leistung                             |               |
| Netzwerk   |   | Energiequelle *                      | Gleichstrom   |
| Netzstandard *                                     | IEEE 802.1p, IEEE 802.3, IEEE 802.3ab, IEEE 802.3u, IEEE 802.3x | Netzteil enthalten *                 | ✓             |
| 10G-Unterstützung *                                | ✗   | Eingangsstrom                        | 0,6 A         |
| Kupfer Ethernet Verkabelungstechnologie            | 10BASE-T, 100BASE-TX, 1000BASE-T                                | Eingangsspannung                     | 5 V           |
| unterstützte Kabeltypen                            | Cat3, Cat4, Cat5, Cat5e   | Ausgangsspannung                     | 9 V           |
| Vollduplex   | ✓   | Ausgangsstrom                        | 0,6 A         |
| Unterstützung Datenflusssteuerung                  | ✓   | Stromverbrauch (max.)                | 2,3 W         |
| Auto MDI/MDI-X                                     | ✓   | Power over Ethernet (PoE)            |               |
| Auto-Negotiation-Funktion                          | ✓   | Power over Ethernet (PoE) *          | ✗             |
| Selbstlernen von MAC-Adressen unterstützt          | ✓   | Betriebsbedingungen                  |               |
| Auto-Änderung von MAC-Adressen unterstützt         | ✓   | Betriebstemperatur                   | 0 - 40 °C     |
| Datenübertragung                                   |   | Temperaturbereich bei Lagerung       | -40 - 70 °C   |
| Routing-/Switching-Kapazität *                     | 10 Gbit/s   | Relative Luftfeuchtigkeit in Betrieb | 10 - 90%      |
| Transferrate                                       | 7,4 Mpps  | Luftfeuchtigkeit bei Lagerung        | 5 - 90%       |
| MAC-Adressentabelle *                              | 2000 Eintragungen   | Wärmeableitung                       | 7,83 BTU/h    |
| Store-and-Forward                                  | ✓   | Gewicht und Abmessungen              |               |
| Jumbo Frames Unterstützung                         | ✓   | Breite                               | 99,8 mm       |
| Jumbo-Frames                                       | 16000   | Tiefe                                | 97,8 mm       |
| Datenpaket-Pufferspeicher                          | 1 MB  | Höhe                                 | 25 mm         |
|  |   | Verpackungsdaten                     |               |
|  |   | Mitgelieferte Kabel                  | AC            |
|  |   | Benutzerhandbuch                     | ✓             |
|  |   | AC-Netzadapter                       | ✓             |
|  |   | Verpackungsart                       | Box           |

| Sicherheit      |         | Verpackungsdaten      |          |
|-----------------|---------|-----------------------|----------|
| IGMP snooping   | ✓       | Gummifüße             | ✓        |
| Design          |         | Verpackungsbreite     | 128 mm   |
| Rack-Einbau *   | ✗       | Verpackungstiefe      | 125 mm   |
| Produktfarbe    | Schwarz | Verpackungshöhe       | 92 mm    |
| Gehäusematerial | Stahl   | Logistikdaten         |          |
|                 |         | Warentarifnummer (HS) | 85176990 |



6935364083519



6935364095024

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.